


## CSI-2004-T800





CSI-2004-T800 Grab & Go Charge and Networked wired Security Cabinet designed for 4 Getac T800 with Hand straps. Dimensions 21.96" W 13.15" D x 23.85" H. Leveling feet, floor/table mounting brackets for rigid placement, and wall mounting brackets.

Rating: Not Rated Yet

**Price**

[Ask a question about this product](#)

### Description

#### CSI-2004 Tablet Cabinet

For Getac T800 Fully Rugged Tablets

#### Description

The CSI-2004 Grab and Go cabinet is designed specifically for up to 4 Getac T800 ruggedized tablets with Handstraps. The grab-and-go style cabinet allows the user to take-out and return tablets without having to worry about plugging them in. Tablets are connected to the cabinet through the proprietary Pogo connector allowing A/C power and network access. To ensure the devices are charged and up to date with software patches the cabinet can accommodate an optional 8 port Cisco switch. This small form factor cabinet is ideal for areas with limited space and can be attached to a wall using the supplied mounting bracket.

#### Features

- Supports up to 4 Getac T800 Fully Rugged Tablets
- Grab-and-Go design makes removal and return fast and easy
- Proprietary Pogo connector eliminates cable mess and connection failure
- Power and Network (Cat 6 Wiring) provided to each slot/ dock
- Top compartment can accommodate a Cisco 8 port switch
- Hinged door with single keyed lock
- Door window allows visibility of power lights on tablets
- Thermostatically controlled fan in top lid

#### Cabinet Specifications

Cabinet is designed to only be used with Getac T800 Fully Rugged

#### Tablets

- Model Number: CSI-2004-T800 Cabinet Dimensions: 23.85"H x 21.96"W x 13.15"D
- Cabinet Weight (Empty): 55 lbs

- Cabinet Max Weight: 120 lbs
- Operating Temperature: 10 - 32+ degrees Celsius
- Wall Mount: Wall Mounting Brackets Supplied

### Cabinet Power Specifications

Cabinet Power Supply is UL Approved

- Voltage: 110VAC or 220VAC
- Current: 12 amps
- Circuit Breaker: 15A (max)
- Frequency: 47-63 Hz
- Overload Protection: Automatic Shutdown and Restart
- Overheat Protection: Automatic Shutdown and Restart

### Docking Slot Specifications

- Docking Station Connector: Proprietary Pogo 24-pin Connector
- Power: 19v DC
- Network: 10/100/1000 base-T Ethernet

### Fan System Specifications

#### - Fan Size:

Dual 120mm x 120mm

- Airflow: 108 CFM | 126 m<sup>3</sup>/h (@ 1,350 RPM)

- Noise Level: 0.3 Sone (@ 1,350 RPM)

- Thermostat: Activated by temperature controller when above 86 Deg F. Foam replaceable debris filters available for each fan

Where to Buy Charge Solutions Inc. Products in the United States

**Contact Charge Solutions Inc. direct to obtain pricing, GSA Pricing Available.**

Charge Solutions Inc.

855-423-3435

[info@chargesolutionsinc.com](mailto:info@chargesolutionsinc.com)



