

## ZH-1000T for Getac T800









CSI – ZH-1000T Grab & Go Charge and Networked wired Security Cabinet designed for 8 Getac T800. Dimensions 18.65" W 11.19" D x 32" H. Wall mounting brackets included.

Rating: Not Rated Yet

**Price**

7 Days



[Ask a question about this product](#)

Description window.dataLayer = window.dataLayer || []; function gtag(){dataLayer.push(arguments);} gtag('js', new Date()); gtag('config', 'UA-74487274-1');

ZH-1000T Tablet Cabinet  
For Getac T800 Fully Rugged Tablets

### Description

The ZH-1000T cabinet is designed specifically for up to 8 Getac T800 ruggedized tablets. The grab-and-go style cabinet allows the user to take-out and return tablets without having to worry about plugging them in. Tablets are connected to the cabinet through the proprietary Pogo connector allowing A/C power and network access. To ensure the devices are charged and up to date with software patches the cabinet can accommodate an optional 8 port Cisco switch. This small form factor cabinet is ideal for areas with limited space and can be attached to a wall using the supplied mounting bracket.

### Features

- Supports up to 8 Getac T800 Fully Rugged Tablets
- Grab-and-Go design makes removal and return fast and easy
- Proprietary Pogo connector eliminates cable mess and connection failure
- Power and Network (Cat 6 Wiring) provided to each slot/ dock
- Top compartment can accommodate a Cisco 8 port switch
- Hinged door with single keyed lock
- Door window allows visibility of power lights on tablets
- Thermostatically controlled fan in top lid

### Cabinet Specifications

Cabinet is designed to only be used with Getac T800 Fully Rugged

### Tablets

- Model Number: ZH-1000T
- Cabinet Dimensions: 32"H x 18.65"W x 11.19"D
- Cabinet Weight (Empty): 75 lbs

- Cabinet Max Weight: 120 lbs
- Operating Temperature: 10 - 32+ degrees Celsius
- Wall Mount: Wall Mounting Brackets Supplied

#### Cabinet Power Specifications

Cabinet Power Supply is UL Approved

- Voltage: 110VAC or 220VAC
- Current: 12 amps
- Circuit Breaker: 15A (max)
- Frequency: 47-63 Hz
- Overload Protection: Automatic Shutdown and Restart
- Overheat Protection: Automatic Shutdown and Restart

#### Docking Slot Specifications

- Docking Station Connector: Proprietary Pogo 24-pin Connector
- Power: 19v DC
- Network: 10/100/1000 base-T Ethernet

#### Fan System Specifications

- Fan Size: 120mm x 120mm
- Airflow: 74 CFM | 126 m3/h (@ 1,350 RPM)
- Noise Level: 0.3 Sone (@ 1,350 RPM)
- Thermostat: 90 Degrees F - 100 Degrees F
- RPM Curve: 400 RPM until 90°F, Up to 1,350 RPM @ 100°F

3 year warranty

Where to Buy Charge Solutions Inc. Products in the United States

**Contact Charge Solutions Inc. direct to obtain pricing, GSA Pricing Available.**

Charge Solutions Inc.

855-423-3435

[info@chargesolutionsinc.com](mailto:info@chargesolutionsinc.com)

